

EnBon

FC D Model

Outdoor Fixed Front And Back Service Design



ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display




Lighter **W**eight **E**asier **O**peration

20% lighter than normal products
Making it more convenient to operate and move




L*H: 250*250(mm)

Module



L*H:500*500(mm)

Cabinet



Weight 7.5kg

ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display



Thinner Panels Lower Cost

6 in 1 flight case saves more space
and transportation cost



24 panels can be placed horizontally
in a regular 20-foot or 40-foot truck

85mm
Panel Thickness



ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display

EnBon

High Refresh Rate

High Grayscale



Low Refresh Rate



High Refresh Rate




Low Grayscale



High Grayscale



Product Details




Can Do Seamless Splicing




Safety Lock



Corner Cover



Power Box



Fast Lock
Between Left and
Right Cabinets

ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display



Stowing **A**nd **H**anging

Optional vertical installation and hanging beam installation



Hanging Beam Installation




Vertical Installation



Front **And** Rear Installation **And** Maintenance

Front and rear installation and maintenance, flexible installation and convenient maintenance



Fixed Installation



Product Specification

Advanced locking system safety, Mechanism enables one-man installation

Pixel Pitch	2.604	2.976	3.91	4.81
LED Lamp	SMD1515	SMD1921	SMD1921	SMD1921
Density (dots/m2)	147456	112896	65536	43264
Brightness	≥3500 nits	≥3500 nits	≥3500 nits	≥3500 nits
IP Rating	IP65	IP65	IP65	IP65
Cabinet Materiel	Die-casting Aluminum			
Scan	32 scan	21 scan	16 scan	13 scan
Module Weight	0.5 kg	0.5 kg	0.5 kg	0.5 kg
Cabinet Weight	7.5 kg	7.5 kg	7.5 kg	8 kg
Module Size (mm)	250*250	250*250	250*250	250*250
Cabinet Size (mm)	500*500*85	500*500*85	500*500*85	500*500*85
Module Pixel	96*96 dots	84*84 dots	64*64 dots	52*52 dots
Cabinet Pixel	192*192 dots	168*168 dots	128*128 dots	104*104 dots
Max Power	600 w/sqm	600 w/sqm	600 w/sqm	600 w/sqm
Average Power	360 w/sqm	360 w/sqm	360 w/sqm	360 w/sqm
Viewing Angle	H140 (+70/-70) deg V140 (+70/-70) deg			
Control Way	Synchronous / Asynchronous			
Gray Scale	16 bit			
Operating System	AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI			
Work Humidity	10% ~ 90%			
Work Temperature	-20 ~ + 65°C			

Shenzhen Enbon Optoelectronic CO.,LTD

3/ F, Building 1, High-tech Park,Fuyuan Road No.156, Fuhai Street,
Fuyong Town,Baoan District, Shenzhen, China



Enbon



Enbon Led Display